

Marine Engine Oil O-278-N

A heavy-duty diesel engine oil

Description:

A high performance engine oil suitable for four stroke diesel engines operating under severe heavy duty conditions.

Pack sizes:

55 Gallon Drum, IBC.

Application:

Four stroke diesel engines operating under severe heavy duty conditions.

Cost Saving Benefits:

- Lower operational costs
Extended oil life due to outstanding viscosity control in combination with excellent base number retention over long period of time.
- Engine cleanliness Excellent clean engine technology that minimizes deposit and sludge build-up throughout the engine
- Enhanced technology
Developed with outstanding quality base oils and excellent additive technology, giving excellent oxidation and thermal stability over prolonged periods of time

Test	Method	Result
Kinematic Viscosity@ 100°C, mm ² /s	D445	13.4
Viscosity Index	D2270	>90
Density @ 15°C, g/ml	D1298	0.893
Flash Point, PMC, °C	D93	>210
Pour Point, °C	D97	<-14
Total Base Number, TBN, mg KOH/g	D2896	12
FZG Gear Test, A/8.3/90, FLS	DIN 51 354	12

Performance Level:

NATO O-278, API CF.

This product information data sheet is based on our general experience and knowledge by the time it went to press and is intended to inform technically experienced readers about possible applications. It is no warranty of product properties or suitability in the individual case. Nor does it release the user from performing preliminary tests with the selected product. We recommend contacting our technical consultants for a discussion of your specific needs. If requested and possible we shall gladly provide samples for testing. IBROMA products are continually improved. IBROMA Lubrication, therefore, reserves the right to change any and all technical information contained in this publication at any time and without prior notice.